

Triflex Uncoupling Membrane DC-Mat



Product information

Applications

Triflex Uncoupling Membrane DC-Mat is used in the Triflex ProDrain system.

Properties

Triflex Uncoupling Membrane DC-Mat is a mat, fleece-backed on both sides, with internal quartz sand chambers and integrated drainage channels.

The mass per unit area is approx. 2.30 kg/m².

The material is approx. 3.2 mm thick.

- Waterproof
- Malleable
- Crack-bridging
- Reduces footfall sound

Pack size

Roll

100 x 500 cm w x l Triflex Uncoupling Membrane DC-Mat

Colours

White

Storage

Triflex DC-Mat Uncoupling Membrane should be stored and transported in its original packaging, keeping it upright, dry and protected against damage from impacts. Store at temperatures between +5 °C and +30 °C. Shelf life of 12 months if unopened.



Conditions for use

Triflex Uncoupling Membrane DC-Mat can be applied at substrate and ambient temperatures between +5 °C and +30 °C.

Instructions for use

See the system description for Triflex ProDrain

General notes

We guarantee the consistently high quality of our products. Non-system substances must not be added to Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for the respective purpose. Technical information is subject to changes without notice in the interests of technical advancement or enhancement of our products.